

EZ

EZ 800

Single-Clip Machine



Easy Clip Line® – for bags

- For closure of bags and nets, including those used as outer packaging
- Firm, safe packaging
- Made of high-quality stainless steel and industrial plastic
- Horizontal version optionally available

Why clip with EZ 800?

The clipping machine EZ 800 of the Easy Clip Line® reliably closes bags and nets. It is primarily employed for the efficient packaging of turkeys and turkey parts in bags. Many other products, including paste-like materials, may also be securely packaged in bags by means of clip closure. The EZ 800 is particularly suited to the closing of large, highstrength bags.



Advantages

- Firm, tight and hygienic packaging due to clip closure
- Automatic clip triggering by insertion of the tail into the slot of the clip guide
- Simple operation
- Integrated pneumatic knife with cut-off valve for shortening the bag tail
- Table top or in-built version, left-hand, with backward-inclined or upright machine on base plate
- Processes high-quality clips – certified safe for use with food by SGS INSTITUT FRESENIUS

- Clip and loop manufacture certified in accordance with ISO 22000



Quality and hygiene

- Hygienic design made of stainless steel and industrial plastic for easy cleaning



Maintenance

- Low maintenance and low wear owing to the small number of moving parts



Optional equipment

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod



Excellence in Clipping

poly-clip®
SYSTEM

at diameters of 35 – 48 mm for horizontal version

- Pressure reducer with filter
- Machine feet (table top version)



Combinability

VAC

Suitable for vacuum packaging and shrink bags, can be combined with the VAC vacuum system



Consumables

S-Clip: S 844, S 848, S 854



Function and operation

The clipping machine EZ 800 operates pneumatically and is designed for the efficient packaging of large poultry. By inserting the tail into the slot of the clip guide, the tail is shirred and the clipping process is triggered automatically. In parallel, the bag tail is cut with the pneumatic knife. This function may alternatively be switched off by the cut-off valve.



EZ 800 horizontal version with mounting bracket and vertical vacuum nozzle for heavy, bulky products

Technical data

Width	256 mm
Depth	335 mm
Height	1,055 mm
Weight	32 kg
Compressed air	5–7 bar / 0,5–0,7 MPa
Air consumption 6 bar	7.9 NL/cycle

Dimensions, weight and consumption values vary depending on the equipment and/or machine configuration.



EZ 800 horizontal version with trolley